

<b>Model</b>	<b>WTL30</b>	<b>UNIT</b>	
<b>Machine Data</b>	Machine weight	kg	1700
	Overall Length without	mm	2600
	Overall Length with Bucket	mm	3270
	Overall Width	mm	1130
	Rated Lift load Without attachment/Retracted	kg	1350
	Extended Dump height	mm	3000
	Retracted Dump height	mm	2480
	Wheel base	mm	1350
	Min Turning Radius	mm	2480
	Turning Angle	o	45
	<b>Engine Data</b>	Make	
Fuel Type			Diesel
Filtration			Donaldson
Model			D1105
Cylinder			3
Displacement		Cm <sup>3</sup>	1123
EU Emission Stage			Tier 4 Final
Max Power		Kw/HP	22 / 28
Rated Speed		rpm	2200
<b>Hydraulic System</b>	Make		<b>Danfoss (Germany)</b>
	Working Pump Type x 2		High Flow Dual/Variable Displacement
	Drive System Pressure	Bar	350
	Drive System Flowrate	L/min	80
	Working System Pressure	Bar	200
	Working System Flowrate	L/pm	70
	Auxiliary Pump Type		Gear
	Auxiliary Circuit Pressure	Bar	190
	Auxiliary Circuit Flowrate	L/pm	52
Drive Motor Type x 4		Dual/Variable Displacement	
<b>Travell</b>	Type		Hydro static 4WD
	Speed (2 Speed modes)	km/h	0-9 / 9- 20
	Traction		X Drive Traction Mode
<b>Quick Connectors</b>	Make		<b>Stauff (Germany)</b>
	Type		Flat Faced G1/2, G3/8 (Quick release no leak type)
<b>Hitch</b>	Type		Mini Universal Quick Hitch
	Function		Electric/Hydraulic
	Spec (W x H)	mm	514 x 226
	Fuel Tank	L	30

<b>Fluid Capacities</b>	Engine oil	L	4.7
	Hydraulic oil	L	40
<b>Tyre</b>	Make		Advance Tubeless
	Spec		26x12-12
<b>Electrical Data</b>	Operating Voltage	V	12